



FIRST AID

UPDATE

February 22, 2010

U.S.A. and Canada: dial 1 800 465-7325

Others: dial (514) 523-8324 (Canada)

Product and company identification:

Product name: Paint Tar Remover for pavers and slabs
Material uses: Use to dissolve sealant, paint, tar or bitumen, rubber and chewing gum on pavers, slabs, concrete and masonry
Supplier/Manufacturer: Techniseal
300, avenue Liberte
Candiac, QC, Canada, J5R 6X1
Tel: (514) 523-2110
Toll free: 1-800-465-7325
Fax: (450) 633-3035

In case of emergency: CANUTEC (613) 996-6666

First aid measures:

Eye contact: Check for and remove any contact lenses. In case of contact with eyes, rinse immediately with plenty of water. Get medical attention.

Skin contact: In case of contact, immediately flush skin with plenty of water for at least 20 minutes. Get medical attention.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. Get medical attention.

Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention.

Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Notes to physician: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Fire-fighting measures:

Flammability of the product: Combustible liquid.

Extinguishing media:

Suitable: Use dry chemical, CO2, water spray (fog) or foam.

Not suitable: Do not use water jet

Special exposure hazards: Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Hazardous thermal decomposition products: Decomposition products may include the following materials: carbon dioxide, carbon monoxide and nitrogen oxides.

Special protective equipment for fire-fighters: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Disposal considerations:

Waste disposal : The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Other information:

Label requirements : COMBUSTIBLE LIQUID AND VAPOR. CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. CONTAINS MATERIAL THAT CAN CAUSE TARGET ORGAN DAMAGE.

Hazardous Material Information System (U.S.A.) :

Health	*	2
Fire hazard		2
Physical Hazard		0
Personal protection		B

HAZARD RATINGS

- 4- Extreme
- 3- Serious
- 2- Moderate
- 1- Slight
- 0- Minimal

See section 8 for more detailed information on personal protection.

The customer is responsible for determining the PPE code for this material.