:: Techniseal®



UPDATE

February 22, 2010

U.S.A. and Canada: dial 1 800 465-7325 Others: dial (514) 523-8324 (Canada)

Product and company identification:

Product name: RG+ POLYMERIC SAND

Material uses: Polymeric sands for pavement joints

Supplier/Manufacturer: Techniseal

300, avenue Liberte

Candiac, QC, Canada, J5R 6X1

Tel: (514) 523-2110

Toll free: 1-800-465-7325

Fax: (450) 633-3035

In case of emergency: CANUTEC (613) 996-6666

First aid measures:

Eye contact: Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 20 minutes. Get medical attention immediately.

Skin contact: In case of contact, immediately flush skin with plenty of water for at least 20 minutes. Get medical attention immediately.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately

Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves **Notes to physician:** No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Fire-fighting measures:

Flammability of the product: Non-flammable

Extinguishing media:

Suitable: Use an extinguishing agent suitable for the surrounding fire.

Not suitable: None known

<u>Hazardous thermal</u>: Decomposition products may include the following materials: carbon dioxide, carbon monoxide and metal oxide/oxides.

Special protective equipment for fire-fighters: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Disposal considerations:

Waste disposal: The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.


Disposal should be in accordance with applicable regional, national and local laws and regulations.

Other information:

Label requirements

: CAUSES RESPIRATORY TRACT, EYE AND SKIN BURNS. CONTAINS MATERIAL THAT CAN CAUSE TARGET ORGAN DAMAGE. CANCER HAZARD - CONTAINS MATERIAL WHICH CAN CAUSE CANCER.

Hazardous Material Information System (U.S.A.)



HAZARD RATINGS

4- Extreme
3- Serious
2- Moderate
1- Slight
0- Minimal
See section 8 for more detailed information on personal protection.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



References : ANSI Z400.1, MSDS Standard, 2004. - Manufacturer's Material Safety Data Sheet. -

29CFR Part1910.1200 OSHA MSDS Requirements. - 49CFR Table List of Hazardous Materials, UN#, Proper Shipping Names, PG. - Canada Gazette Part II, Vol. 122, No. 2. Registration SOR/88-64, 31 December 1987. Hazardous Products Act "Ingredient Disclosure List" - Canadian Transport of Dangerous Goods, Regulations and Schedules,

Clear Language version 2005.

Date of issue : 11/15/2008
Date of previous issue : 10/30/2008
Version : 1.1