



WET LOOK

Paver Protector (WLS)



UPDATE

February 4, 2011

Make sure that you have an up-to-date technical data sheet in hand by consulting our Web site: techniseal.com

U.S.A. and Canada: dial 1 800 465-7325
Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- Recommended for driveways, parking lots, patios and walkways

PROPERTIES

- Enhances paver color
- Optimal oil repellency
- Water-based

DESCRIPTION

Made of modified acrylic and alkyd hybrid dispersion, TECHNISEAL[®] Wet-look PAVER PROTECTOR (WLS) is a semi-gloss, microporous and transparent coating that protects pavers made of concrete while enhancing their original color. It reduces oil and dirt penetration, and makes cleaning easier. Easy to apply, it penetrates the surface for maximum adhesion and durability. Wet-look PAVER PROTECTOR will not peel or discolor. It resists the elements (freeze-thaw cycles, sun, rain, etc.), as well as calcium and salt. It also resists hot tire pick-up. Water-based, Wet-look PAVER PROTECTOR does not give off unpleasant fumes and is environmentally friendly.

DIRECTIONS

BEFORE YOU BEGIN:

Wear adequate protective clothing.

ALWAYS TEST the product on a small hidden area of approximately 4 sq. ft. to ensure the results will meet your expectations. Do not thin or dilute. Keep from freezing.

Apply only to bare material, to material that has been previously sealed with this product.

Recoating: Wait until the surface of the PROTECTOR is worn before recoating (minimum of 2 years).

New concrete pavers: Efflorescence (whitish salt) may appear on such materials within 60 days following installation. Wait at least 60 days before cleaning and sealing. Applying a PROTECTOR before 60 days may cause blotchiness of the surface.

Newly installed polymeric sand on older pavers: Wait at least 30 days before cleaning and sealing pavers.

Slipperiness: This product can make the surface more slippery when wet. The application of a matte finish PROTECTOR such as the COLOR BOOST (WLP) is recommended where slipperiness represents a cause for concern.

Light-grey pavers: These types of surfaces may show uneven color shading after application of a PROTECTOR that offers color enhancement. Always test a small section of pavers to ensure the results meet the desired aesthetic.

Results will vary according to paver type, porosity and color. Proper surface priming is essential.

PREPARATION:

Stain removal: Remove any stains (oil, rust, etc.) from the surface using the appropriate TECHNISEAL® stain remover.

Priming: This step is essential to obtain an optimal and uniform result. Prime the entire surface by removing all efflorescence and ground-in dirt. This ensures a uniform look and allows the PROTECTOR to better penetrate the surface. Use TECHNISEAL® PAVER PRIMER/EFFLORESCENCE CLEANER for pavers with efflorescence or pavers less than 5 years old. Use Techniseal® HC HARDSCAPE CLEANER for surfaces without efflorescence or pavers more than 5 years old.

APPLICATION:

- Surface must be clean, dry (24 hours without precipitation) and warm to the touch (morning).
- Joints must also be dry.
- Temperature must be between 50°F and 80°F and rain should not be forecasted over the following 24 hours.
- Sprinklers must be shut off.
- For optimal results, apply product under constant weather conditions and using the same application method from start to finish.
- Shake container or stir product before use.

Roller application: Using a regular foam roller (non-slit) and a paint tray, saturate the surface with a first coat of PROTECTOR.

Sprayer application: Soak the surface using an airless or pump sprayer. The level of saturation obtained will determine the intensity of the wet-look.

Wait until PROTECTOR is dry and apply a second coat. Product is dry when it turns from a grey liquid to a clear film. As each coat is being applied, back-roll any excess PROTECTOR with a foam roller, before it dries.

Stepping on freshly applied PROTECTOR could leave marks on pavers.

Let dry for 24 hours before walking on the surface and 48 hours before allowing traffic.

Cleaning of tools: Use water and soap.

Cleaning yearly with TECHNISEAL® HC HARDSCAPE CLEANER will keep pavers looking fresh.

COVERAGE

1 gallon covers up to 150 sq. ft. per coat. Coverage will depend on the porosity and temperature of the treated surface. It is recommended that a small area be tested to determine the exact amount needed.

STORAGE and SHELF LIFE

Product must be kept in its original, unopened and tightly sealed container and stored in a dry and well ventilated place with controlled temperature (40°F to 75°F). Keep sheltered from weather and direct sunlight. Properly stored, the product's shelf life is 3 years following production (see date on packaging).

PACKAGING

Product Code	Pro Size	Units per box	Units per pallet
121-333	1 gal	4	180
121-336	5 gal.	-	48
221-338	55 gal.	-	4

WARNING

MAY CAUSE SKIN AND EYE IRRITATION. **CONTAINS:** Acrylic Polymers. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. **KEEP OUT OF REACH OF CHILDREN. FIRST AID:** In case of contact, immediately flush eyes and skin with plenty of water. If irritation persists, get medical attention. Calculated VOC: <100 g/L.

FOR MORE INFORMATION, CONSULT THE MATERIAL SAFETY DATA SHEET

SHIPPING

Land and sea

NOT REGULATED

LIMITED WARRANTY

Manufacturer, having no control over the use of the materials, does not guarantee finished work. Replacement of any defective product shall be the buyer's sole remedy under this warranty. A proof of purchase will be required for any claim. Before using this product, user shall determine the suitability of the product for its intended use and user alone assumes all risks and liability whatsoever in connection therewith. User shall test product in a small inconspicuous area (approx. 4 sq. ft.) under projected conditions of use. In the event that no test was carried out, the warranty will only apply to 4 sq.ft. (0.4 m²). This limited warranty excludes any liability for any consequential, incidental, indirect or special damages. Except for the limited warranty made above, manufacturer specifically disclaims and excludes any other express warranty, any implied warranty of merchantability of goods and implied warranty of fitness of goods for any particular purpose.