




# AQUALINE®


4 1/2 X 9  
PERMEABLE PAVER

LOW MAINTENANCE AND PROVEN DURABILITY THAT ALLOWS FOR FLEXIBLE DESIGN OPTIONS

## PALLET LAYOUT



Stacked Bond Pallet Layout




90° Herringbone Pallet Layout


## FEATURES & BENEFITS

- Interlocking spacer bars for increased structural performance
- Smooth surface texture with a micro-chamfer to minimize vibration and enhance wheelchair comfort
- Can be utilized to construct an ADA-compliant pavement
- True installed dimensions for design optimization
- Optimal joint openings for infiltration and maintenance
- Chamfer Width: 3 mm
- Spacer Bar Width: 10 mm
- Surface Infiltration Rate: > 500 inches per hour (varies based on joint infill gradation)
- Surface Open Area: 10%

## LAYING PATTERNS




RUNNING BOND



HERRINGBONE

Visit [BelgardCommercial.com](http://BelgardCommercial.com) for more options.

Mechanical Installation Available 

Contact your local Belgard® representative for details and mechanical availability.

Belgard permeable pavers can be used for a variety of different vehicular applications. Appropriate shape and thickness is based on project-specific conditions, including type of loading, base design, and subgrade conditions. It is recommended that you consult a Belgard Representative when specifying products for vehicular applications.

Check with your local Belgard Representative for product availability and color options.

## SHAPES & SIZES

PAVER



4 1/2 x 9 x 3/8"

**BELGARD®** PAVES THE WAY™

For more info, visit [BelgardCommercial.com](http://BelgardCommercial.com)

Oldcastle APG - A CRH Company  
400 Perimeter Center Terrace, Suite 1000  
Atlanta, GA 30346  
1-844-495-8210



© 2020 Oldcastle® APG, Inc. All Rights Reserved. BELCOMM20-202